

## Guzzler



Blower: Positive Displacement Dual-Lobe or Tri-Lobe Available  
Bolt-On Dumptubes

Maximum Vacuum Range: 16-28.5 Hg (0.93 kg/cm<sup>2</sup>)

Customized Ultra-Quiet Silencer Maximum Airflow Range: 5,089-6,000 cfm (8,647 cm<sup>3</sup>/hr)

Bag Cleaning: Baghouse Is Equipped with a 120 psi Bag-Cleaning Pulsation System

Drive: Air-Shifted Transfer Case with  
Manual Override

Liquid Level Float Ball Shut-Off

Color-Coded, Function-Stamped, Wiring Harness

**First Stage:** Radial Deflection Wing

**Second Stage:** Cyclone Centrifugal Separator

**Third Stage:** Sixty 70" Dacron Filter Bags (5 Micron); 10.72:1 Air-to-Cloth Ratio

Decant Valves

Hydraulics: Hydraulic Pump Driven by PTO; Hydraulic System Plumbing

Assembled Using JIC Fittings and Hydraulic Tubing

50-Gallon (189.25-Liter) Hydraulic Tank

6" Air-Operated Relief Valve

Heavy-Duty Subframe

Inline Vacuum Relief Valve

Payload Capacity: 18 yd<sup>3</sup>-21 yd<sup>3</sup>

Rear Door Prop

Collector Body: 1/4" (16.35 mm) Thick

### Construction:

Rear Bulkhead Is 3/8"

(9.525 mm) Thick Plate with Lower-Edge Reinforcement

Tailgate Is 1/2" (12.7 mm) Thick, Supported by Two Heavy-Duty Hinges

50° Dump Height and 15" (38.1 cm) Rear Overhang

### Controls:

Tachometer

Blower Hourmeter

Pulsation System Air Pressure Gauge

Hydraulic System Pressure Gauge

Blower Vacuum Gauge

Blower Temperature Gauge

Hydraulic Rear Door: Single-Lever

Unlock/Open and Close/Lock

Single-Mode Filtration System

Debris Body Prop

Back-Up Alarm

Roadside Emergency Kit and

Fire Extinguisher



24 Hour 7 Days A Week **On Call** Service  
Delivery Nationwide Available  
Quality Inspected Equipment Before Rental  
Combined 80 Years Experience

**www.AquaBlasters.com**  
sales@aquablasters.com  
**281-842-9990** Office  
**1-866-362-9332** Toll Free